

2-Wire Analyzer

FLXA202

- Clear touch panel display
- Support of up to two sensors
- Robust die-cast aluminum case

Robust case


- FLXA202 offers rugged die-cast aluminum case.



The Pinnacle of 2-wire Analyzer!

Support of up to two sensors

- Through the installation of up to two sensors, FLXA202 realizes interruption-free measurement even during maintenance.



SENCOM™ Smart digital sensor

- SA11 SENCOM™ Smart adapter combined with dedicated sensor can be used as digital sensor.



Clear touch panel display

- Improved operability through touch panel screen of 2-wire analyzer
- Clear display and user-friendly indication with 12 languages



Specifications

Refer to the GS sheets for the detailed specifications.

FLXA202	
Measurement	pH/ORP, Conductivity (SC), Inductive conductivity (ISC), Dissolved oxygen (DO), Digital sensor (SA11 SENCOM SMART Adapter): pH/ORP, conductivity
Housing	Aluminum die casting
Outline dimension	165 (W) x 165 (H) x 155 (D) mm
Weight	Approx. 2.5 kg
Display	Black/White LCD with a touch screen
Mounting	Pipe, wall or panel mounting
Environmental conditions	-20 to 55°C
Power supply	1 input 16 to 40 V DC (pH/ORP, SC, DO) 17 to 40 V DC (ISC) 21 to 40 V DC (SA11 SENCOM SMART Adapter) 2 inputs 22.8 to 40 V DC (pH/ORP, SC, DO)
Output signal	4-20 mA DC
Hazardous location approvals	ATEX, IECEx, FM, CSA, NEPSI, EACEx KOSHA
Communication	HART



Relevant Product

SA11 SENCOM SMART Adapter

- Available measurement: pH/ORP, conductivity
- SENCOM SMART Adapter offers the ability to do all sensor maintenance and calibrations in the laboratory which can reduce operating cost.




Mobile Field Device Management **FieldMate**

- The dedicated screen is prepared for SENCOM™ Smart adapter SA11.
- Directly connects to SA11 and calibration and setting at off-site room.
- Ability to calibrate up to 4 pH sensors at the same time.
- Database management system for different serial numbers of sensor.



4 sensors display



4 sensors calibration display

OpreX™ Yokogawa achieves operational excellence by providing products, services, and solutions based on the OpreX comprehensive brand that cover everything from business management to operations.

Trademarks

Co-innovating tomorrow, OpreX and all product names of Yokogawa Electric Corporation in this bulletin are either trademarks or registered trademarks of Yokogawa Electric Corporation. All other company brand or product names in this bulletin are trademarks or registered trademarks of their respective holders.

YOKOGAWA ELECTRIC CORPORATION

World Headquarters

9-32, Nakacho 2-chome, Musashino-shi, Tokyo 180-8750, JAPAN

<http://www.yokogawa.com/an/>

YOKOGAWA CORPORATION OF AMERICA

YOKOGAWA EUROPE B.V.

YOKOGAWA ENGINEERING ASIA PTE. LTD.

YOKOGAWA CHINA CO., LTD.

YOKOGAWA MIDDLE EAST & AFRICA B.S.C.(c)

<http://www.yokogawa.com/us/>

<http://www.yokogawa.com/eu/>

<http://www.yokogawa.com/sg/>

<http://www.yokogawa.com/cn/>

<http://www.yokogawa.com/bh/>

Represented by:

ANA-01E

Subject to change without notice.

All Rights Reserved, Copyright © 2015, Yokogawa Electric Corporation.

[Ed:02/b]

Printed in Japan, 012(KP)